

70

ESSENTIAL SERIES

ACUTARB120 DECK MOUNTED POT FILLER

DESCRIZIONE DESCRIPTION




DECK MOUNTED POT FILLER

DATI TECNICI TECHNICAL INFO

TOP SPESSORE MASSIMO - TOP THICKNESS MAXIMUM	1 15/16"
TOP SPESSORE MINIMO - TOP THICKNESS MINIMUM	3/8"
NUMERO FORI - NUMBER OF HOLES	1
DIAMETRO FORO - FITTING HOLE DIAMETER	Ø 1 3/2" - 1 9/16"
DISTANZA TRA COLLEGAMENTI MIN - INLET SUPPLY SPREAD MINIMUM	/
DISTANZA TRA COLLEGAMENTI MAX - INLET SUPPLY SPREAD MAXIMUM	/
COLLEGAMENTO IDRICO - HOSE OR INLET CONNECTION SIZE	1/2" Male NPT
LUNGHEZZA ATTACCO FLESSIBILE - HOSE CONNECTION LENGTH	17 11/16"
ALTEZZA TOTALE - TOTAL HEIGHT	14 9/16" in
ALTEZZA GETTO - SPOUT HEIGHT	11 7/16"
LUNGHEZZA GETTO - SPOUT REACH	Min: 9 13/16" - Max: 11 13/16"
GETTO GIREVOLE - SPOUT SWIVEL	Yes
NUMERO MANOPOLE - NUMBER OF HANDLES	1
MATERIALE BASE - PRIMARY MATERIAL	Brass
TIPO INSTALLAZIONE - INSTALLATION TYPE	TOP Mounted
MATERIALE VALVOLA - VALVE MATERIAL	Ceramic
PRESSIONE DELL'ACQUA - WATER PRESSURE	70,0 / 20,0 / 45,0 psi
SUGGERITO APPLICATION	Bar, Kitchen, Laundry
HANDLE SPREAD MINIMUM	/
HANDLE SPREAD MAXIMUM	/

DISEGNO TECNICO TECHNICAL DRAWINGS



A = 9 13/16" or 11 13/16" mm
A = 250 o 300 mm