


# 70

ESSENTIAL SERIES

## ACUTAOG06L

POT FILLER

### DESCRIZIONE DESCRIPTION



### POT FILLER

### DATI TECNICI TECHNICAL INFO

TOP SPESSORE MASSIMO - TOP THICKNESS MAXIMUM	/
TOP SPESSORE MINIMO - TOP THICKNESS MINIMUM	/
NUMERO FORI - NUMBER OF HOLES	/
DIAMETRO FORO - FITTING HOLE DIAMETER	/
DISTANZA TRA COLLEGAMENTI MIN - INLET SUPPLY SPREAD MINIMUM	/
DISTANZA TRA COLLEGAMENTI MAX - INLET SUPPLY SPREAD MAXIMUM	/
COLLEGAMENTO IDRICO - HOSE OR INLET CONNECTION SIZE	1/2" female NPT (USA)
LUNGHEZZA ATTACCO FLESSIBILE - HOSE CONNECTION LENGTH	/
ALTEZZA TOTALE - TOTAL HEIGHT	14 9/16"
ALTEZZA GETTO - SPOUT HEIGHT	/
LUNGHEZZA GETTO - SPOUT REACH	20 9/16"
PORTATA - FLOW RATE	1.2 gpm
GETTO GIREVOLE - SPOUT SWIVEL	Yes
NUMERO MANOPOLE - NUMBER OF HANDLES	2
MATERIALE BASE - PRIMARY MATERIAL	Brass
TIPO INSTALLAZIONE - INSTALLATION TYPE	Wall Mounted
MATERIALE VALVOLA - VALVE MATERIAL	Ceramic
PRESSIONE DELL' ACQUA - WATER PRESSURE	70,0 / 20,0 / 45,0 psi
SUGGERITO APPLICATION	Bar, Kitchen, Laundry
HANDLE SPREAD MINIMUM	/
HANDLE SPREAD MAXIMUM	/

### DISEGNO TECNICO TECHNICAL DRAWINGS

