

70

ESSENTIAL SERIES

ACUTAOG06P

POT FILLER

DESCRIZIONE DESCRIPTION



POT FILLER

DATI TECNICI TECHNICAL INFO

| | |
|---|------------------------|
| TOP SPESSORE MASSIMO - TOP THICKNESS MAXIMUM | / |
| TOP SPESSORE MINIMO - TOP THICKNESS MINIMUM | / |
| NUMERO FORI - NUMBER OF HOLES | / |
| DIAMETRO FORO - FITTING HOLE DIAMETER | / |
| DISTANZA TRA COLLEGAMENTI MIN - INLET SUPPLY SPREAD MINIMUM | / |
| DISTANZA TRA COLLEGAMENTI MAX - INLET SUPPLY SPREAD MAXIMUM | / |
| COLLEGAMENTO IDRICO - HOSE OR INLET CONNECTION SIZE | 1/2" female NPT (USA) |
| LUNGHEZZA ATTACCO FLESSIBILE - HOSE CONNECTION LENGTH | / |
| ALTEZZA TOTALE - TOTAL HEIGHT | 14 9/16" |
| ALTEZZA GETTO - SPOUT HEIGHT | / |
| LUNGHEZZA GETTO - SPOUT REACH | 20 9/16" |
| PORTATA - FLOW RATE | 1.2 gpm |
| GETTO GIREVOLE - SPOUT SWIVEL | Yes |
| NUMERO MANOPOLE - NUMBER OF HANDLES | 2 |
| MATERIALE BASE - PRIMARY MATERIAL | Brass |
| TIPO INSTALLAZIONE - INSTALLATION TYPE | Wall Mounted |
| MATERIALE VALVOLA - VALVE MATERIAL | Ceramic |
| PRESSIONE DELL' ACQUA - WATER PRESSURE | 70,0 / 20,0 / 45,0 psi |
| SUGGERITO APPLICATION | Bar, Kitchen, Laundry |
| HANDLE SPREAD MINIMUM | / |
| HANDLE SPREAD MAXIMUM | / |

DISEGNO TECNICO TECHNICAL DRAWINGS

